

**42396A-1****Butterfly Hanger for 1-1/4 in coaxial cable and elliptical waveguide 64**

Dimensions

Nominal Size	1-1/4 in
Compatible Diameter, maximum	43.180 mm 1.700 in
Compatible Diameter, minimum	37.592 mm 1.480 in
Height	59.00 mm 2.32 in
Length	76.20 mm 3.00 in
Width	38.10 mm 1.50 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

General Specifications

Hanger Type	Standard butterfly hanger
Cables per Hanger	1
Color	Silver
Material Type	Stainless steel
Ordering Note	CommScope® standard product in the United States and Canada
Package Quantity	10

Mechanical Specifications

Corrosion Resistance, minimum with no degradation	=500 hours in salt spray chamber
Mounting	3/8 in (M10) drilled cable ladder
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Vibration Survival	=4 hours at resonant frequency
Environmental Strength Capability	Double cable weight

Packed Dimensions

Height	26.0 cm 10.2 in
Length	9.0 cm 3.5 in
Shipping Weight	0.53 kg 1.16 lb
Width	9.0 cm 3.5 in

Regulatory Compliance/Certifications

Agency	Classification
--------	----------------

Product Specifications

COMMScope®

42396A-1

RoHS 2011/65/EU

China RoHS SJ/T 11364-2006

ISO 9001:2008

Compliant

Below Maximum Concentration Value (MCV)

Designed, manufactured and/or distributed under this quality management system

