

-GENESIS-

Riser Rated Security & Control Cable

Part Number: 2229

16 AWG 3 Stranded Conductors Shielded

Ratings	CMR, CL3R, FPLR, FT4 Sunlight Resistant
Approvals	ETL Listed
<u>Construction</u>	
Conductor	16 AWG 19 Strand Bare Copper
Conductor Count	3
Insulation	Polypropylene (0.007" nom.)
Insulation Colors	Black, Red, White
Lay Length	3" nom.
Shielding	Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord	Yes
Jacket	PVC (0.015 " nom.)
Overall Diameter	0.186" nom.
Print Legend	GENESIS P/N 2229 3C16 SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4 SUN RES 75C (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9
<u>Properties</u>	
Operating Voltage	300 Volts max.
DC Resistance	4.19 Ohms/1000' at 20°C
Capacitance	37.3 pF/ft. nom.
Impedance	40 Ohms nom.
Temperature	-20 °C to 75 °C
Flame Rating	UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant	Yes
Country of Origin	USA