



Fanvil Y501-Y/Y501W-Y/Y501-Y-E/Y501W-Y-E SIP Healthcare Intercom

Fanvil Y501-Y series SIP healthcare intercoms are specially designed for home-based care, nursing house and other indoor application, realizing the emergency communication, security protection, broadcasting, etc. They feature HD audio, 2 SIP accounts, detachable DSS keys, IP54 waterproof and dustproof, and built-in 2.4G & 5G Wi-Fi(Y501W-Y/Y501W-Y-E). Y501-Y series provide different installation modes of standard 86 box embedded and wall mountable, bringing you a timely healthcare communication experience.

Highlights

- ✓ Support audio codec G.722 and Opus.
- ✓ Support specific 433MHz wireless button
- ✓ Features 2 SIP accounts and 6 antibacterial material detachable function buttons
- ✓ Support HD audio with codec G.722 and Opus
- ✓ Built-in 2.4G&5G Wi-Fi(Y501W-Y/Y501W-Y-E)
- ✓ Built-in 1 short circuit input/output interface
- ✓ IP54 waterproof and dustproof
- ✓ Support PoE power supply
- ✓ Support wall mountable installation (Y501-Y/Y501W-Y) and 86 box embedded installation(Y501-Y-E/Y501W-Y-E)



Model	Network	Button	PoE	Wi-Fi
Y501-Y	10/100Mbps	6	✓	×
Y501W-Y	10/100Mbps	6	✓	2.4G&5G Wi-Fi
Y501-Y-E	10/100Mbps	6	✓	×
Y501W-Y-E	10/100Mbps	6	✓	2.4G&5G Wi-Fi

Generic

- 2 SIP Lines
- Auto answer
- HD Voice
- PoE Enabled
- Built-in 2.4GHz & 5G Wi-Fi(Y501W-Y/Y501W-Y-E)
- Intercom function
- External Power Supply (Optional)

Intercom Function

- Support customized DSS keys
- Support wireless button (Optional)
- Network Time Synchronization
- Built-in Wi-Fi
 - 2.4G, 802.11 b/g/n
 - 5G, 802.11 a/n
- Action URL / Active URL

Audio

- Narrowband Codec: G.711a/u, G.729AB, G.723.1, G.726, iLBC
- Wideband Codec: G.722, Opus
- Duplex intercom with Acoustic Echo Canceller (AEC)

- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay (RFC2833) / SIP INFO

Networking

- Physical: 10/100 Mbps Ethernet
- WIFI: 2.4G & 5G (Y501W-Y/Y501W-Y-E)
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static / DHCP / PPPoE
- Wi-Fi Encryption: WPA /WPA2-PSK /802.X EAP
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP

- IPv6
- LLDP
- PPPoE
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Deployment & Maintenance

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Firmware Upgrade
- Syslog

Physical Specifications

- Y501-Y Series: 6 DSS buttons (Finish, Nursing, Assistant, Call, Dressing change, Infusion)
- Up to 10 wireless buttons supported
- Status indicator light: Red(registration failed、network anomaly)、Green(registration successful、call)
- 1 RJ45 port

- 1 short circuit input interface
- 1 relay: NC/NO Contacts, Max DC30V/1A, AC125V/0.5A
- Power: DC12V/1A or POE
- Power Consumption (Adapter):
 - 0.94W~1.98W(Y501-Y/Y501-Y-E)
 - 1.42W~2.35W(Y501W-Y/Y501W-Y-E)
- Power Consumption (PoE):
 - 1.48W~2.37W(Y501-Y/Y501-Y-E)
 - 1.99W~3.05W(Y501W-Y/Y501W-Y-E)
- Housing material: ABS
- 433 wireless button specification:
 - communication mode: FSK
 - working frequency: 433MHZ
 - communication protocol: Ebelong1.1
- Installation: Indoor installation
 - Standard 86 Box Embedded
 - Wall Mountable
- Color: White
- working temperature: -10 ~50 °C
- Storage temperature: -20 ~ 50 °C
- Relative humidity: 10% - 90%
- N.W/CNT: 3.97kg
- G.W/CNT: 4.4 kg
- Equipment Dimension:
 - 87.56 x 87.56 x 30mm (Wall Mountable)
 - 87.56 x 87.56 x 21.5mm (86 Box Embedded)
- Packing Dimension: 234x168x44 mm
- Outer CTN Dimension: 356x245x254mm (10pcs)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.
For more information, please visit: www.fanvil.com

www.fanvil.com

Add:10/F Block A, Dualshine Global Science Innovation Center,Honglang North 2nd Road, Bao'an District, Shenzhen, China, 518100

Tel: +86-755-2640-2199 Fax: +86-755-2640-2618 Email: sales@fanvil.com

